

IPTables - Forwarding

Between LAN and WLAN

Add the following to `/etc/udev/rules.d/10-network.rules`, substitute `LAN_MAC_ADDR` and `WLAN_MAC_ADDR` with your Ethernet device and WLAN device MAC addresses for persistent network names:

```
SUBSYSTEM=="net", ACTION=="add", ATTR{address}=="LAN_MAC_ADDR", NAME="ether0"  
SUBSYSTEM=="net", ACTION=="add", ATTR{address}=="WLAN_MAC_ADDR", NAME="wifi0"
```

Add the following to `/etc/sysctl.d/30-ip_forward.conf`:

```
net.ipv4.ip_forward=1  
net.ipv4.conf.default.forwarding=1  
net.ipv4.conf.all.forwarding=1  
Add the following to /etc/iptables/iptables.rules:  
*nat  
: PREROUTING ACCEPT [ 783: 65928]  
: INPUT ACCEPT [ 73: 9660]  
: OUTPUT ACCEPT [ 6180: 382480]  
: POSTROUTING ACCEPT [ 18: 1260]  
-A POSTROUTING -o wifi0 -j MASQUERADE  
COMMIT  
  
*filter  
: INPUT ACCEPT [ 0: 0]  
: FORWARD ACCEPT [ 0: 0]  
: OUTPUT ACCEPT [ 176: 192839]  
-A INPUT -i lo -m comment --comment "Inbound from loopback (lo)" -j ACCEPT  
-A INPUT -m state --state RELATED,ESTABLISHED -j ACCEPT  
-A INPUT -p icmp -j ACCEPT  
-A INPUT -j NFLOG --nflog-group 1  
-A INPUT -j REJECT --reject-with icmp-host-prohibited  
-A FORWARD -i wifi0 -j ACCEPT  
-A FORWARD -i wifi0 -o ether0 -m comment --comment "ether0 <- wifi0" -j ACCEPT  
-A FORWARD -i ether0 -o wifi0 -m comment --comment "wifi0 -> ether0" -j ACCEPT  
-A FORWARD -j REJECT --reject-with icmp-host-prohibited  
COMMIT
```

Revision #1

Created 11 April 2017 21:02:24 by Tingwai

Updated 17 April 2017 18:33:05 by Tingwai